

- 21 -

## Claims

1. A method for distributing IN services between mobile networks, comprising the steps of:

- 5 a) providing a service trader function in at least one of said mobile networks, said service trader function providing a location information of distributed IN services;
- 10 b) checking said service trader function, when a location update procedure is performed; and
- c) updating a service trigger information in accordance with the checking result.

15 2. A method according to claim 1, wherein said service trader function is provided at least in the home network of a mobile subscriber.

20 3. A method according to claim 1 or 2, wherein said service trader function provides an information about networks and service control points to which IN services have been downloaded.

25 4. A method according to any one of the preceding claims, wherein said service trigger information is a CAMEL subscriber information.

30 5. A method according to claim 4, wherein said location information provided by said service trader function comprises at least a gsmSCF address and a service key.

6. A method according to any one of the preceding claims, wherein said trader function comprises a function for

- 22 -

searching an IN service on the basis of a subscriber language and/or service attributes.

7. A method according to any of the preceding claims,  
5 further comprising the step of performing a rerouting to an actual location of said IN service, when said IN service is not available at the location indicated by said location information.

10 8. A method according to claim 7, wherein said rerouting is performed by said service trader function.

9. A method according to claim 7, wherein said rerouting  
15 is performed by a service controller of said mobile network.

10. A method according to claim 9, wherein said service controller is the CSE of the GSM.

20 11. A method for distributing IN services to a mobile network, comprising the steps of:  
a) providing a service trader function in said mobile network, said service trader function providing a location information of distributed IN services;  
25 b) checking said service trader function, as to the location of an IN service, when said IN service is triggered; and  
c) sending the IN service invocation to the location of said IN service.

30

- 23 -

12. A method according to claim 11, wherein said IN service is downloaded from said location of said IN service.

5 13. A method according to claim 11 or 12, wherein said checking step is performed in a mobile switching center (MSC).

10 14. A method according to any one of claims 11 to 13, wherein said service trader function (STF) is arranged to obtain a service controller address of an IN service in a visited network based on a home service controller address of said IN service, when said IN service is downloaded from the home network to said visited network.

15 15. A method according to any one of claims 11 to 13, wherein said service trader function provides a function for selecting a voice service information.

20 16. A system for distributing IN services to a mobile network, comprising:

- a) service trader means (STF) for providing a location information of distributed IN services; and
- b) location register means (HLR) for checking said
- 25 service trader means (STF) in response to a location update procedure;
- c) wherein said location register means (HLR) is arranged to update a service trigger information in accordance with the checking result.

30